



Section 4 Earth Terminals Type WK/WKN...SL/U

Description	U-foot 4mm ²	U-foot 6mm ²
DIN VDE 0611 Part 3/11.89	finely stranded single core V A 0.5-4mm ² 0,5-6mm ² 750V~/900V -*)34**)	finely stranded single core V A 0,5-6mm ² 0,5-10mm ² 750V~/900V -*)44**)
DIN VDE 0611 Part 3/11.89	800V/8kV/3	800V/8kV3*)
UL-Data	No. 22-10 AWG 600V*)	No. 22-8 AWG 600V*)
CSA-Data	No. 22-10 AWG	No. 22-8 AWG
Width	6mm	8mm
stripping length	9mm	12mm
Approvals		



	Ref No	Part No	Box Qty	Ref No	Part No	Box Qty
Earth Terminal with U-foot colour: yellow/green	WKN4SLU	57.504.9055.0	10	WKN6SLU	57.506.9055.0	10
	WKN4SLU²⁾	57.504.9055.0	10	WKN6SLU²⁾	57.506.9055.0	10

EEx e earth terminal with U-foot ¹⁾

Accessories

1. Mounting rail 35, DIN rail 7.5 high (plain)	TS35P	98.300.0000.0	5	TS35P	98.300.0000.0	5
Mounting rail 35, DIN rail 15 high	TS35HD	98.370.0000.0	5	TS35HD	98.370.1000.0	5
Mounting rail 35, DIN rail 7.5 high (slotted)	TS35S	98.300.1000.0	5	TS35S	98.300.1000.0	5
Mounting rail 32, G rail	TS32G	98.190.0000.0	5	TS32G	98.190.0000.0	5

*) Measurements to adjacent feedthrough clamp of identical size and series.

**) Mounting rail loading see Parts Catalogue 8, page 12.

1) Clamps require certification. The information currently stated in the certificate applies (e.g. 660V).

2) Certificate for EEx e-approval : EEx e II A5EV 91.1 B11638U.

= Stock items

Tel: +44 (0) 1302 873996

Fax: +44 (0) 1302 872798

www.mcg-products.com